

## **Technical data:**

|                              |                                   |                                                      |
|------------------------------|-----------------------------------|------------------------------------------------------|
| Connections                  | Graphic / Keyboard / Mouse        | 1 x HDDB-37                                          |
|                              | Power supply                      | 1 x DC-12V                                           |
| Connection cable (included ) | PS/2 / USB / HDMI Combo           | HLS-H01 (1.2m)                                       |
| Switch                       | LCD settings                      | 5 Pressure switches                                  |
|                              | ON / OFF                          | 1 Pressure switch                                    |
|                              | OFF (LCD folded)                  | 1 Semi-covert pressure switch                        |
| LED-Display panel            | Operation                         | 1 x green/red                                        |
|                              | Number                            | 1 x blue                                             |
|                              | Capital letters                   | 1 x blue                                             |
|                              | Scroll                            | 1 x blue                                             |
| Emulation                    | Keyboard/ Mouse                   | USB and PS/2                                         |
|                              | Display                           | Yes                                                  |
| Graphic                      | 17" LCD                           | 1280 x 1024                                          |
|                              | Colors                            | 16,2 Mio.                                            |
|                              | Frame Rate                        | H: 31,0 KHz. – 81,0 KHz.<br>V: 56,0 KHz. – 76,0 KHz. |
|                              | Viewing angle                     | H: 140° / V: 130°                                    |
|                              | Bandwith                          | 140 Mhz.                                             |
|                              | Brightness                        | 300 cd/m <sup>2</sup>                                |
|                              | Contrast                          | 700 : 1                                              |
|                              | Reaktion time                     | 4 ms.                                                |
|                              | Pixel pitch                       | 0,264mm (H) x 0,264mm (V)                            |
|                              | Backlight                         | LED                                                  |
| Input values                 | 100 V. – 240 V. AC, 48 Hz – 62 Hz |                                                      |
| Output values                | DC 12V., 4,16A                    |                                                      |
| Power consumption            | 230 V / 18,8 Watt                 |                                                      |
| Certification                | RoHS, RoHS2, CE                   |                                                      |
| Environment                  | Operating temperature             | -10 - 50°C                                           |
|                              | Storage temperature               | -20 – 60°C                                           |
|                              | Humidity                          | 0 – 80% relative humidity (non condensing)           |
| Physical properties          | Casing                            | High performance steel                               |
|                              | Color                             | RAL 9005                                             |
|                              | Weight                            | 14.0 kg incl. angles                                 |
|                              | Dimension (L x W x H) w/o handle  | 410 x 450 x 44.5mm (19" / 1U)                        |
|                              | Dimension (L x W x H) w. handle   | 422 x 450 x 44,5mm (19" / 1U)                        |
| Packaging                    | Weight                            | 15.0 kg                                              |
|                              | Dimension (L x W x H)             | 74 x 62 x 18 cm                                      |