

Technical data:

Connections KVM	Graphic / Keyboard / Mouse	4 / 8 / 16 / 32 x RJ-45
	Keyboard / Mouse external	2 x USB-A
	Power supply	1 x DC-12V
	External Monitor	1 x HDDB-15 (only AK-1732-K5)
	Remote Extender	1 x RJ-45 (only AK-1732-K5) Extender KL-151 or KL-153 optional
Connections (Standard)	1x VGA und 1x USB Standard (within delivery)	4 / 8 / 16 / 32 x KD-DON-USB Standard
	1x VGA und 2x PS/2 Optional	KD-DON-PS/2 Optional
Switch	LCD settings	5 Pressure switch
	ON / OFF	1 Pressure switch
	OFF (LCD folded)	1 Semi-covert pressure switch
LED-Display panel	Operation	1 x green/red
	Number	1 x blue
	Capital letters	1 x blue
	Scroll	1 x blue
LED-Display KVM	Port/Switch	16 x green (Port)
Emulation	Keyboard/ Mouse	USB & PS/2
	Display	JA
Port selection	Hotkey / OSD	
Graphic	17" LCD	1280 x 1024
	Colors	16,2 Mio.
	Frame Rate	H: 31,0 KHz. – 81,0 KHz. V: 56,0 KHz. – 76,0 KHz.
	Viewing angle	H: 140° / V: 130°
	Bandwith	140 Mhz.
	Brightness	300 cd/m ²
	Contrast	700 : 1
	Reaktion time	4 ms.
	Pixel pitch	0,264mm (H) x 0,264mm (V)
	Backlight	LED
Input values	100 V. – 240 V. AC, 48 Hz – 62 Hz	
Output values	DC 12V., 4,16A	
Power consumption	230 V / 14,6 Watt	
Certification	RoHS, RoHS2, CE	
Environment	Operating temperature	-10 - 50°C
	Storage temperature	-20 – 60°C
	Humidity	0 – 80% relative humidity (non condensing)
Physical properties	Casing	High performance steel
	Color	RAL 9005
	Weight	16.8 kg incl. angles
	Dimension (L x W x H) w/o handle	555 x 450 x 44,5mm (19" / 1U)
	Dimension (L x W x H) w. handle	567 x 450 x 44,5mm (19" / 1U)
Packaging	Weight	17.8 kg
	Dimension (L x W x H)	74 x 62 x 18 cm