

## **Technical data:**

|   |                                      |   |
|---|--------------------------------------|---|
| Connections KVM                                 | Graphic / Keyboard / Mouse           | 8 / 16 HDDB-15  |
|   | External (HUB)                       | 3 X USB-Typ-A   |
|   | Power supply                         | 1 x DC-12V  |
| Connection cable (not included in the delivery) | USB / PS2/VGA combo                  | KAB-102-4 (1,8m), KAB-103-4 (3,0m)<br>KAB-105-4(5,0m) |
|   | USB / VGA                            | KAB-102U-1 (1,8m)                                     |
| Switch  | LCD settings                         | 4 Pressure switch                                     |
|   | ON / OFF                             | 1 Pressure switch                                     |
|   | OFF (LCD folded)                     | 1 Semi-covert pressure switch                         |
| LED-Display panel                               | Operation                            | 1 x green   |
|   | Number                               | 1 x green   |
|   | Capital letters                      | 1 x green   |
|   | Scroll                               | 1 x green   |
| LED-Display KVM                                 | Port/Switch                          | 8 / 16 x green (Port)                                 |
|   |                                      | 8 / 16 x red (USB)                                    |
| Emulation                                       | Keyboard/ Mouse                      | USB & PS/2  |
|   | Display                              | Yes   |
| Graphic   | 17" LCD                              | 1920 x 1080   |
|   | Colors                               | 16,2 Mio.   |
|   | Frame Rate                           | H: 31,0 KHz. – 81,0 KHz.<br>V: 56,0 KHz. – 76,0 KHz.  |
|   | Viewing angle                        | H: 140° / V: 130°                                     |
|   | Bandwith                             | 140 Mhz.  |
|   | Brightness                           | 300 cd/m <sup>2</sup>                                 |
|   | Contrast                             | 700 : 1   |
|   | Reaktion time                        | 4 ms.   |
|   | Pixel pitch                          | 0,264mm (H) x 0,264mm (V)                             |
|   | Backlight                            | LED   |
| Input values                                    | 100 V. – 240 V. AC, 48 Hz – 62 Hz    |   |
| Output values                                   | DC 12V., 4,16A                       |   |
| Power consumption                               | 230 V / 14,6 Watt                    |   |
| Certification                                   | RoHS, RoHS2, CE                      |   |
| Environment                                     | Operating temperature                | 0 – 40°C  |
|   | Storage temperature                  | -20 – 60°C  |
|   | Humidity                             | 0 – 80% relative humidity (non condensing)            |
| Physical properties                             | Casing                               | High performance steel                                |
|   | Color                                | RAL 9005  |
|   | Weight                               | 12,9 kg incl. angles                                  |
|   | Dimension (L x W x H) without handle | 64,00 x 43,6 x 4,4cm (19" / 1U)                       |
|   | Dimension (L x W x H) with handle    | 68,20 x 43,6 x 4,4cm (19" / 1U)                       |
| Packaging                                       | Weight                               | 17,1 kg   |
|   | Dimension (L x W x H)                | 77,5 x 58 x 21 cm                                     |