

Technical data:

Connections KVM	Graphic / Keyboard / Mouse	1 x HDDB-15
	USB HUB	1 x USB 2.0 Typ-A
	External (Front-HUB)	3 x USB 2.0 Typ-A
	Power supply	1 x C13 IEC socket
Connection cable (included)	USB / PS/2 / VGA Combo	KAB-102-4 (1,8m)
	USB-Hub	1 x USB-A-A (1,8m)
Optional Connection cable	USB / PS/2 / VGA Combo	KAB-103-4 (3,0m), KAB-105-4 (5,0m)
Switch	LCD settings	4 Pressure switch
	ON / OFF	1 Pressure switch
	OFF (LCD folded)	1 Semi-covert pressure switch
LED-Display panel	Operation	1 x green
	Number	1 x green
	Capital letters	1 x green
	Scroll	1 x green
Emulation	Keyboard/ Mouse	USB & PS/2
	Display	Yes
Graphic	19" LCD	1280 x 1024
	Colors	16,2 Mio.
	Frame Rate	H: 31,0 KHz. – 82,0 KHz. V: 60,0 KHz. – 75,0 KHz.
	Viewing angle	H: 140° / V: 130°
	Bandwith	140 Mhz.
	Brightness	300 cd/m ²
	Contrast	700 : 1
	Reaktion time	4 ms.
	Pixel pitch	0,264mm (H) x 0,264mm (V)
	Backlight	LED
Input values	100 V. – 240 V. AC, 48 Hz – 62 Hz	
Output values	DC 12V., 4,16A	
Power consumption	230 V / 19,6 Watt	
Certification	RoHS, RoHS2, CE	
Environment	Operating temperature	0 – 40°C
	Storage temperature	-20 – 60°C
	Humidity	0 – 80% relative humidity (non condensing)
Physical properties	Casing	High performance steel
	Color	RAL 9005
	Weight	12,9 kg incl. angles
	Dimension (L x W x H) without handle	64,00 x 43,6 x 4,4cm (19" / 1U)
	Dimension (L x W x H) with handle	67,80x 43,6 x 4,4cm (19" / 1U)
Packaging	Weight	17,1 kg
	Dimension (L x W x H)	77,5 x 58 x 21 cm